

SOW 系列单级双吸泵系水平中开蜗壳式离心泵性能参数

泵型号	流量Q		扬程 (m)	转速 (rpm)	功率 (kW)	效率 (%)	心需汽蚀余 量 (m)	泵重 (kg)	
	(m <sup>3</sup> /h)	(L/s)							
80-220(I)		22.0	6.1	17.0	1480	5.5	82	1.6	181
		83.5	23.2	13.8					
		121.0	33.6	10.0					
	A	20.0	5.6	14.8					
		77.2	21.4	11.8					
		108.0	30.0	8.7					
	B	17.5	4.86	12.4					
		70.4	19.6	9.8					
		96.0	26.6	7.7					
	C	16.0	4.4	10.6					
		64.4	17.9	8.2					
		83.0	23.0	6.8					
		60.0	16.7	64.5	2950	37	82	4.5	181
		164.5	45.7	55.0					
		240.0	66.7	40.0					
	A	59.0	16.3	58.0					
		152.9	42.5	47.5					
		219.0	60.8	34.0					
	B	55.0	15.3	49.0					
		138.5	38.5	39.0					
		199.0	55.3	30.0					
C	52.0	14.4	42.0						
	128.4	35.7	33.5						
	170.0	47.0	27.5						
80-220		17.0	4.7	16.0	1480	4	81	1.7	181
		66.5	18.5	12.8					
		108.0	30.0	7.8					
	A	16.0	4.4	13.9					
		61.1	17.0	10.8					
		98.0	27.2	7.0					
	B	15.0	4.2	11.8					
		55.8	15.5	9.0					
		85.0	23.6	6.2					
	C	14.5	4.0	10.0					
		51.3	14.3	7.6					
		72.0	20.0	6.1					
		60.0	16.6	62.0	2950	30	81	3.5	181
		134.5	37.4	51.0					
		218.0	60.6	32.0					

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	A	58.0 124.2 197.0	16.1 34.5 54.7	53.5 43.5 28.0		30	80		
	B	57.0 11.3 170.0	15.8 31.4 47.2	45.0 36.0 25.0		22	78.2		
	C	55.5 105 142.0	15.2 29.2 39.4	37.8 31.0 24.0		18.5	74		
80-280 (I)		26.0 104.5 138.0	7.2 29.0 38.3	24.5 22.5 18.0	1480	11	78.5	2.3	1.94
	A	25.0 96 129.0	6.9 26.7 35.8	22.0 19.0 16.0		11	78		
	B	22 88.1 116.0	6.1 24.5 32.2	19.5 16.0 13.0		7.5	76		
	C	21.0 79.4 105.0	5.8 22.0 29.0	16.8 13.0 10.5		5.5	75		
		80.0 208.0 280.0	2.0 57.8 77.8	107.0 90.0 77.5	2950	75	78.5	6.3	1.94
	A	78.0 192.4 235.0	21.7 53.4 65.3	92.5 77.0 68.0		75	77.5		
	B	75.0 174.7 220.0	20.8 48.5 61.1	77.5 63.5 55.0		55	76		
	C	74.0 155.0 200.0	20.5 43.0 55.6	64.0 50.0 45.0		37	75		
80-280		22.0 86.0 112.0	6.1 23.9 31.1	25.9 20.7 16.5	1480	7.5	77	1.9	194
	A	21.0 80.0 102.0	5.8 22.3 28.3	21.8 18.1 14.3		7.5	76		

泵型号	流量Q		扬程 (m)	转速 (rpm)	功率p (kW)	效率 (%)	必需汽蚀余量 (m)	泵重 (kg)
	(m <sup>3</sup> /h)	(L/s)						

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	B	19.5 73.2 92.0	5.4 20.3 25.5	18.7 15.0 12.0	1480	5.5	75	1.9	194
	C	18.0 66.8 82.0	5.0 18.6 22.8	15.8 12.5 10.5		4	74		
		60.0 172.0 220.5	16.7 47.8 61.2	102.0 82.5 66.0	2950	75	77	6.8	194
80-280	A	58.0 160.0 203.0	16.1 44.4 56.3	88.0 71.5 57.0		55	76.2		
	B	57.0 146.7 188.5	15.8 40.8 52.3	74.0 60.0 49.0		45	75.2		
	C	56.0 132.6 170.0	15.5 36.8 47.2	61.0 49.0 40.0	30	74.4			
80-350(I)		29.0 114.4 150.0	8.1 31.8 41.7	43.5 38.8 29.3	1480	22	71.5	2.3	204
	A	26.0 105.5 133.0	7.2 29.3 36.9	37.5 33.0 25.0		15	70.5		
	B	22.0 96.3 117.0	6.1 26.8 32.5	32.0 27.5 22.0		15	70		
	C	20.0 87.5 102.0	5.6 24.2 28.3	26.0 22.5 17.9		11	67.5		
80-350		26.0 100.0 132.0	7.2 27.8 36.7	43.0 35.5 27.9	1480	15	73	2.5	204
	A	22.0 93.1 120.0	6.1 25.9 33.3	37.0 30.8 23.0		15	70		
	B	20.0 82.8 98.0	5.6 23.0 27.2	31.0 25.5 22.8		11	66		
	C	18.0 70.0 71.0	5.0 19.4 19.7	24.0 20.0 19.0		7.5	64		
100-260(I)		38.0	10.6	23.5	1480			2.4	207

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

		145.0 212.0	40.3 58.9	18.8 13.1		11	82.5			
	A	37.0 132.9 192.0	10.3 36.9 53.0	20.1 15.8 11.5		11	81			
	B	36.0 122.9 173.0	10.0 34.1 48.1	17.0 13.5 10.2		7.5	79			
	C	34.0 115.9 154.0	9.4 32.2 42.8	14.5 11.0 8.9		5.5	77.5			
		148.5 289.0 375.0	41.3 80.3 104.2	90.0 75.0 62.0	2950	90	85.5	7.1	207	
	A	120.8 264.9 340.0	33.6 73.6 94.0	88.5 63.0 52.9		75	80.5			
	B	70.0 240.6 325.0	19.4 66.8 90.3	67.5 52.0 43.5		55	79			
	C	60.0 223.4 295.0	16.7 62.0 81.9	57.2 44.8 36.0		45	78			
	100-260		30.0 123.5 170.0	8.3 34.3 47.2	21.7 17.0 12.5	1480	11	81.5	1.9	207
		A	28.0 114.0 154.0	7.8 31.7 42.8	19.0 14.5 11.3		7.5	79.5		
		B	26.0 105.9 143.0	7.2 29.4 39.7	16.3 12.5 9.2		7.5	78		
		C	25.0 99.3 131.0	6.9 27.6 36.4	13.3 11.0 7.9		5.5	76		

泵型号	流量Q		扬程 H (m)	转速 (rpm)	功率 (kW)	效率 (%)	必需汽蚀余量 (m)	泵重 (kg)
	(m <sup>3</sup> /h)	(L/s)						
100-260	52.0	14.4	88.0	2950	75	81.5	7.4	207
	245.5	68.2	68.0					
	340.0	94.4	50.5					
	51.5	14.3	76.0					

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	A	227.7 310.0	63.3 86.1	58.5 53.5		55	79.5			
	B	50.5 212.6 280.0	14.0 59.0 77.8	65.0 51.0 37.0		45	77.5			
	C	49.0 195.0 260.0	13.6 54.2 72.2	55.0 43.0 31.5		37	76			
100-320(I)		47.0 185.5 225.0	13.1 51.5 62.5	38.1 31.2 26.0	1480	22	810	2.6	223	
	A	42.0 172.0 204.0	11.7 47.9 56.7	33.2 27.0 22.5		18.5	79.6			
	B	38.0 157.5 184.0	10.6 43.8 51.1	27.9 22.5 18.5		15	79.3			
	C	37.0 142.8 165.0	10.3 39.7 45.8	23.2 18.5 16.0		11	79			
		185.0 368.0 450.0	51.4 102.2 125.0	148.0 123.0 102.0	2950	200	80	11	223	
	A	140.0 341.6 410.0	38.9 94.9 113.9	130.0 106.0 89.5		132	79.6			
	B	100.0 314.8 370.0	27.7 87.4 102.8	110.0 90.0 77.3		110	79.3			
	C	119.0 245.4 325.0	33.1 68.2 90.3	93.5 74.0 64.0		90	79			
	100-320		50.0 141.5 174.0	13.9 39.3 48.3	36.0 29.5 25.5	1480	18.5	78	2.2	223
		A	48.0 131.6 164.0	13.3 36.6 45.6	31.0 25.5 21.6		15	77.6		
		B	47.0 120.0 152.0	13.1 33.3 42.2	26.0 21.2 17.9		11	77.3		
			44.0	12.2	21.5					
C		112.4	31.2	17.0	11		77			

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

		143.0	39.7	14.1					
		70.0	19.4	146.0		132	78		
		283.0	78.6	119.0					
		350.0	97.2	101.0					
	A	65.0	18.1	125.0		110	77.6		
		263.3	73.1	103.0					
		360.0	100.0	87.0					
	B	61.3	17.0	106.0	2950	90	7.3	9.5	223
		237.8	66.0	84.0					
		310.0	86.1	72.0					
C	60.9	16.9	88.0		75	77			
	215.5	60.0	69.0						
	287.0	79.7	58.0						
100-400(I)		70.0	19.4	63.0		45	73	2.5	241
		185.5	51.5	52.0					
		241.5	67.0	39.0					
	A	65.0	18.1	53.0	1480	30	72		
		170.6	47.4	44.0					
		213.0	59.2	34.0					
	B	62.0	17.2	46.0		30	71		
		158.6	44.0	38.0					
	190.0	52.8	31.2						
C	58.0	16.1	35.5		18.5	69			
	141.6	39.3	30.3						
	178.0	49.4	22.5						
100-400		60.0	16.7	60.9	1480	37	72	3.1	241
		163.0	45.3	52.0					
		217.0	60.3	41.1					
	A	58.0	16.1	50.2		30	69		
		149.9	41.6	44.0					
		188.0	52.2	35.0					

泵型号	流量Q		扬程 (m)	转速 (rpm)	功率 (kW)	效率 (%)	必需汽蚀余量 (m)	泵重 (kg)	
	(m <sup>3</sup> /h)	(L/s)							
100-400	B	54.0	15.0	42.9	1480	22	66.5	3.1	241
		138.4	38.5	37.5					
		168.0	46.7	31.0					
	C	51.0	14.2	33.5	18.5	63			
		121.1	33.6	28.7					
		135.0	37.5	25.8					
125-240(I)		100.0	27.8	20.2	1480	18.5	85.5	1.8	249
		274.6	76.3	14.8					
		370.0	102.8	9.1					

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	A	92.0	25.6	18.3	2950	15	84.5	6.8	249
		259.3	72.0	13.2					
		332.0	92.2	8.3					
	B	82.0	22.8	15.9		15	82.5		
		232.4	64.5	10.6					
		285.0	79.2	7.6					
	C	78.0	21.7	13.2		11	77.5		
		210.5	58.5	8.7					
		240.0	66.7	6.8					
125-240		139.5	38.7	83.5	2950	132	85.5	6.8	249
		533.5	148.2	60.0					
		715.0	198.6	40.0					
	A	124.0	34.4	73.0		110	84		
		496.7	138.0	52.0					
		650.0	180.6	36.0					
	B	119.0	33.1	63.5		75	82		
		454.3	126.2	43.5					
		550.0	152.8	32.0					
C	103.0	28.6	63.0	75	77				
	411.6	114.3	34.0						
	460.0	127.8	30.0						
125-240		100.0	27.8	20.2	1480	15	84.5	2.2	249
		256.5	71.2	15.1					
		320.1	88.9	10.8					
	A	94.0	26.1	17.6		15	84		
		242.5	67.4	13.5					
		300.4	83.4	9.1					
	B	90.0	25.0	15.0		11	82		
		223.8	62.2	11.5					
		265.0	73.6	8.4					
C	82.0	22.8	12.4	7.5	78				
	199.1	55.3	9.1						
	220.0	61.1	7.8						
125-240		111.0	30.8	84.0	2950	110	84.5	8.7	249
		472.5	131.2	60.5					
		662.0	183.9	40.0					
	A	106.0	29.4	73.5		90	84		
		442.2	122.8	53.0					
		592.0	141.7	36.5					
	B	102.0	28.3	62.8		75	82		
		393.7	109.4	42.0					
		510.0	141.0	33.5					
	90.0	25.0	52.5						

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	C	369.5 415.0	102.6 115.0	37.0 33.0		75	77				
125-300(I)		100.0 270.0 375.0	27.8 75.0 104.2	32.5 27.0 21.0	1480	30	84	1.9	274		
	A	80.3 243.7 348.0	22.3 67.7 96.7	27.5 22.0 15.5						22	82
	B	75.0 220.5 310.0	20.8 61.2 86.1	23.5 18.0 12.5							
	C	60.5 195.8 270.0	16.8 54.4 75.0	19.0 14.2 10.5						15	78
		380.0 535.5 640.0	105.6 148.8 177.8	120.0 108.0 92.6	2950	200	84	7.6	274		
	A	285.0 483.4 630.0	79.2 134.3 175.0	103.5 88.0 77.8						160	82
	B	190.0 473.2 600.0	52.8 121.5 166.7	92.0 72.0 60.0							
	C	90.2 389.0 500.0	25.1 108.1 138.9	80.0 57.0 43.5						110	78

泵型号	流量Q		扬程 (m)	转速 (rpm)	功率 (kW)	效率 (%)	必需汽蚀余量 (m)	泵重 (kg)			
	(m <sup>3</sup> /h)	(L/s)									
125-300		100.0 242.5 370.0	27.8 67.4 102.8	32.0 25.0 17.1	1480	30	83	1.9	274		
	A	90.3 222.3 290.0	25.1 61.8 80.6	26.3 21.0 5.0						18.5	82
	B	80.0 202.9 250.0	22.2 56.4 69.4	22.1 17.5 132.2							
	C	70.1 179.5 210.0	19.5 49.9 58.3	17.3 13.7 11.9						11	76
		230.0	63.9	122.0	2950			7.9	274		
		479.0	133.1	100.0		200	83				

SOW 系列单级双吸泵系水平中开蜗壳式离心泵



		580.0	161.1	82.0					
	A	182.0 437.7 540.0	50.5 121.6 150.0	106.2 83.5 63.5		160	82		
	B	128.0 400.8 510.0	35.6 111.3 141.7	89.0 70.0 51.0		110	79		
	C	85.0 355.2 428.0	23.6 98.7 118.9	72.0 55.0 42.0		90	76		
125-380(I)		125.0 310.5 435.0	340.7 86.3 120.8	53.1 47.0 37.5	1480	75	80	2.1	298
	A	104.0 282.8 395.0	28.9 78.6 109.7	45.0 39.0 31.8		45	79		
	B	93.0 254.2 350.0	25.8 70.6 97.2	36.9 31.5 25.0		37	78		
	C	85.5 221.9 295.2	23.7 61.6 109.8	27.9 24.0 18.8		30	76		
125-380		100.2 278.0 396.5	27.8 77.2 110.0	50.2 43.0 33.1	1480	55	79	2.4	298
	A	92.1 257.9 349.6	25.8 71.6 97.1	42.9 37.0 28.4		45	78		
	B	84.0 234.1 300.0	23.3 65.0 83.3	35.9 30.5 24.1		30	77		
	C	79.1 209.8 250.5	22.0 58.3 69.6	28.9 24.5 20.0		22	76		
125-480(I)		1 09.2 328.5 380.4	30.3 9 1.3 1 05.7	86.0 7' 6.0 7 1.0	1480	11 0	80	2.3	331
	A	100.0 307.3 350.9	27.8 85.4 97.4	74.9 66.5 55.0		90	78.5		
	B	80.4 282.0 300.4	22.3 78.3 83.4	64.7 56.0 51.3		75	77		

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	C	60.0 250.4 270.4	16.6 69.6 75.1	54.6 44.2 40.8		45	76		
125-480		100.0 294.5 370.0	27.8 81.8 102.8	81.2 69.5 61.5	1480	90	79	2.7	331
	A	90.1 274.8 320.2	25.0 76.3 88.9	70.0 60.5 55.1		75	78		
	B	85.3 257.2 284.5	23.7 71.4 79.0	60.9 53.0 46.1		55	77		
	C	78.5 230.0 238.8	21.8 63.9 66.3	51.2 43.5 41.3		37	76		
150-280(I)		160.0 443.5 609.0	44.4 123.2 169.2	27.5 21.0 14.2	1480	37	87	2.4	347
	A	150.5 410.6 550.0	41.8 114.0 152.8	25.0 18.0 12.5		30	86		

泵型号		流量Q		扬程 (m)	转速 (rpm)	功率 (kW)	效率 (%)	心需汽蚀余量 (m)	泵重 (kg)
		(m <sup>3</sup> /h)	(L/s)						
150-280(I)	B	130.0 367.0 480.0	36.1 101.9 133.3	22.5 15.0 11.7	1480	22	84	2.4	347
	C	123.0 338.2 395.0	34.1 93.9 109.7	17.4 11.5 10.0		18.5	77		
150-280		140.0 397.0 525.0	38.9 110.3 145.8	27.5 20.4 14.2	1480	30	86	2.5	347
	A	135.0 364.4 496.0	37.5 100.7 137.8	24.1 17.0 11.9		30	85		
	B	128.0 340.7 446.0	35.6 94.6 123.9	21.8 14.5 10.8		22	84		
	C	120.0 318.1 380.0	33.3 88.4 105.6	17.5 11.5 9.3		18.5	80		
150-350(I)		180.0	50.0	45.8	1480			2.5	359

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

		447.5 592.0	124.3 164.4	38.5 31.2		75 85		
	A	175.0 404.2 580.0	48.6 112.3 161.1	38.6 31.0 22.4		55 83		
	B	162.0 363.0 495.0	45.0 100.8 137.5	33.1 25.0 18.1		37 81		
	C	150.0 324.7 421.0	41.7 90.2 116.9	27.0 20.0 14.9		30 78		
150-350		150.0 407.5 550.0	41.7 113.2 152.8	45.0 35.0 26.8	1480	55 84	3.0	359
	A	140.0 374.1 471.0	38.9 103.9 130.8	37.9 29.5 23.2		45 82		
	B	130.0 344.4 460.0	36.1 95.7 127.8	32.1 25.0 17.5		37 80		
	C	125.0 311.9 390.0	34.7 86.6 108.3	26.1 20.5 15.3		30 78		
150-450(I)		200.0 515.5 640.0	55.6 143.2 177.8	76.1 66.0 57.1	1480	132 82	3.4	436
	A	190.0 468.4 600.0	52.8 130.1 166.7	64.0 54.5 45.0		110 81		
	B	180.0 418.5 540.0	50.0 116.3 150.0	52.3 43.5 35.0		75 80		
	C	175.0 375.4 498.0	48.6 104.3 130.0	42.1 35.0 27.8		55 78.5		
150-450		150.0 440.0 582.0	41.7 122.2 161.7	72.1 60.0 48.2	1480	110 81	3.7	436
	A	140.0 401.7 550.0	38.9 111.6 152.8	60.0 50.0 36.9		90 80.5		
		129.0	35.8	49.5				

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	B	359.3 490.0	99.8 136.1	40.0 30.5		75 80		
	C	115.0 326.3 430.0	31.9 90.6 119.4	40.0 33.0 24.8		45 78		
150-570(I)		200.0 584.0 730.0	55.6 162.2 202.8	121.0 105.0 92.1	1480	250 80	4.2	646
	A	180.0 536.2 660.0	50.0 148.9 183.3	105.0 88.5 80.5		200 79		
	B	169.0 493.6 620.0	46.9 137.1 172.2	90.8 75.0 68.0		160 78		
	C	150.0 450.0 530.0	41.7 125.0 147.2	77.2 61.5 55.9		132 77		

泵型号	流量Q		扬程 (m)	转速 (rpm)	功率 (kW)	效率 (%)	心需汽蚀余量 (m)	泵重 (kg)	
	(m <sup>3</sup> /h)	(L/s)							
200-530	B	240.0	66.7	68.3	1480	160	3.0	840	
		633.0	175.8	55.0					
		820.0	227.8	46.1					
	C	230.0	63.9	54.8					
		576.3	160.1	43.5					
		720.0	200.0	38.0					
200-660(I)		280.0	77.8	167.0	1480	450	3.1	990	
		793.0	220.3	150.0		80			
		935.0	259.7	140.0					
	A	270.0	75.0	144.0		355			78.5
		729.7	202.7	127.0					
		900.0	250.0	115.0					
	B	260.0	72.2	124.0		315			77
		669.8	186.0	107.0					
		864.0	240.0	93.0					
	C	250.0	69.4	10.0		250			76
		637.4	177.0	88.0					
		770.0	213.9	80.0					
250-390(I)		400.0	111.1	50.0	1480	160	2.8	665	
		1052.0	292.2	39.0					
		1450.0	402.8	28.0					
	A	380.0	105.6	44.9		132			86

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

		1310.0	363.9	24.0					
	B	379.0 915.3 1160.0	105.3 254.3 322.2	38.0 27.0 20.2		110	83		
	C	350.0 843.3 990.0	97.2 234.3 275.0	31.8 20.0 16.1		75	77.5		
250-390		400.0 1030.5 1400.0	111.1 286.3 388.9	50.0 37.0 25.6	1480	132	87	4.0	665
	A	390.0 958.3 1290.0	108.3 266.2 358.3	44.0 32.0 22.0		110	86		
	B	375.0 880.3 1170.0	104.2 244.5 325.0	38.0 27.0 21.8		110	84		
	C	350.0 819.6 1030.0	97.2 227.7 286.1	32.0 22.0 16.0		75	82		
250-470(I)		420.0 1174.5 1608.0	116.7 326.3 447	82.8 66.0 50.0	1480	280	87	3.3	830
	A	400.0 1072.2 1450.0	111.1 297.8 402.8	69.0 55.0 41.6		220	85		
	B	370.0 975.2 1250.0	102.8 270.9 347.2	58.0 45.5 36.0		20	83		
	C	330.0 903.3 1090.0	91.7 250.9 302.8	49.6 37.5 31.2		160	80		
250-470		400.0 1081.0 1450.0	111.1 300.3 402.8	75.0 54.5 38.0	1480	220	84	3.5	830
	A	370.0 1003.9 1300.0	102.8 278.9 361.1	64.0 47.0 33.5		220	82.5		
	B	350.0 911.0 1170.0	97.2 253.0 325.0	55.0 40.5 30.0		160	80.5		
	C	340.0 830.0 1020.0	94.4 230.6 283.3	46.0 34.5 26.3		110	78.5		

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

泵型号		流量Q		扬程 H (m)	转速 n (rpm)	功率 p (kW)	效率 n (%)	必需汽 蚀余量 (m)	泵重 W (kg)
		(m <sup>3</sup> /h)	(L/s)						
250-610(I)		800.0	222.2	131.0	1480	560	84	3.8	1215
		1234.0	345.3	116.0					
		1640.0	455.6	98.0					
	A	750.0	208.3	115.0					
		1154.1	320.6	110.0					
		1600.0	444.4	79.0					
	B	700.0	194.4	95.0					
		1051.4	291.0	83.0					
		1480.0	411.1	63.0					
	C	650.0	180.6	78.0					
		970.0	269.4	66.0					
		1360.0	377.8	50.0					
250-610		400.0	111.1	126.0	1480	400	83	3.1	1215
		1045.0	290.3	104.0					
		1415.0	393.1	81.5					
	A	390.0	108.3	110.0					
		972.1	270.0	90.0					
		1360.0	377.8	70.0					
	B	380.0	105.6	91.0					
		884.5	245.7	74.5					
		1240.0	344.4	58.0					
	C	335.0	101.4	75.0					
		806.9	224.1	62.0					
		1120.0	311.1	49.5					
300-330(I)		500.0	138.9	36.0	1480	110	86	6.3	630
		1099.0	305.3	24.5					
		1475.0	409.7	17.0					
	A	480.0	133.3	31.8					
		1020.0	283.3	19.8					
		1425.0	395.8	12.1					
	B	460.0	127.8	26.5					
		970.0	269.4	15.5					
		1290.0	358.3	9.0					
	C	440.0	122.2	22.3					
		920.0	255.6	11.5					
		1170.0	325.0	7.5					
300-330		400.0	111.1	32.1	1480	90	85	3.6	630
		940.0	261.1	23.0					
		1260.0	350.0	15.0					

S0W 系列单级双吸泵系水平中开蜗壳式离心泵

	A	390.0 876.6 1200.0	108.3 243.5 333.0	27.9 20.0 12.0		75	84		
	B	370.0 801.0 1080.0	102.8 222.5 300.0	24.1 16.7 11.0		55	81		
	C	350.0 705.0 950.0	97.2 195.8 263.9	20.5 13.7 9.0		37	77		
300-450(I)		700.0 1678.5 2380.0	194.4 466.3 661.1	67.5 53.0 37.0	1480	215	88	5.2	905
	A	660.0 1576.8 2100.0	183.3 438.0 583.3	59.2 45.0 32.0		280	86.5		
	B	620.0 1476.0 1800.0	172.2 410.0 500.0	50.0 36.5 27.5		200	84		
	C	600.0 1360.0 1450.0	166.7 378.0 402.8	41.0 27.5 24.5		160	79		
300-450		600.0 1620.0 2240.0	166.7 450.0 622.2	68.0 51.5 32.5	1480	315	87.5	5.3	905
	A	580.0 1519.2 2040.0	161.1 422.0 566.7	60.0 45.0 29.4		250	86.5		
	B	560.0 1422.0 1860.0	155.6 395.0 516.7	51.0 37.5 26.2		200	84		
	C	540.0 1332.0 1620.0	150.0 370.0 450.0	41.9 30.5 23.5		160	81.5		
300-550(I)		700.0 1750.0 2350.0	194.4 486.1 652.8	115.0 94.0 76.0	1480	630	86	4.2	1425
	A	680.0 1645.2 2170.0	188.9 457.0 602.8	92.0 76.0 61.5		450	85.5		
300-550(I)	B	650.0 1573.2 2130.0	180.6 437.0 591.7	77.5 62.0 47.0	1480	355	85	4.2	1425

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	C	620.0 1515.6 1980.0	172.2 421.0 550.0	65.0 50.0 37.5		280	83.5		
300-550		600.0 1550.0 2130.0	166.7 430.5 591.7	102.0 80.0 60.0	1480	450	84.5	3.9	1425
	A	590.0 1447.2 1980.0	163.9 402.0 550.0	86.4 67.0 50.5		355	83.5		
	B	580.0 1360.8 1820.0	161.1 378.0 505.6	73.0 57.0 44.0		280	83		
	C	570.0 1281.6 1600.0	158.3 356.0 461.1	61.0 47.5 37.2		250	82		
300-710(I)		900.0 1836.0 2100.0	250.0 510.0 583.3	183.0 160.0 150.6	1480	1120	85	3.5	1690
	A	960.0 1735.2 2030.0	266.7 482.0 563.9	160.0 136.0 126.0		900	84.6		
	B	800.0 1623.6 1880.0	222.2 451.0 522.2	135.0 112.0 104.0		630	84.3		
	C	700.0 1537.2 1600.0	194.4 427.0 444.4	110.5 91.0 77.0		560	84		
300-710		600.0 1690.0 2160.0	166.7 469.4 600.0	174.0 139.0 118.0	1480	900	83.5	4	1690
	A	580.0 1573.0 2000.0	161.1 431.0 555.6	150.0 119.0 100.0		710	83		
	B	540.0 1450.8 1800.0	150.0 403.0 505.6	124.0 99.0 82.4		560	82.5		
	C	510.0 1342.8 1650.0	141.7 373.0 458.3	103.0 81.0 70.0		400	82		
350-380(I)		600.0 1733.0 2280.0	166.7 481.4 633.3	45.5 32.0 20.5	1480	200	86.5	6.2	865
		580.0	161.1	40.0					

SOW 系列单级双吸泵系水平中开蜗壳式离心泵



	A	1692.0 2160.0	470.0 600.0	26.5 17.0		160	85		
	B	560.0 1641.6 2080.0	155.5 456.0 577.8	34.0 21.0 12.8		132	83		
	C	540.0 1602.0 1900.0	150.0 445.0 527.8	27.9 15.0 9.0		110	80.5		
350-380		500.0 1424.0 1940.0	38.9 395.6 538.9	42.5 31.0 21.8	1480	160	85.5	5	865
	A	460.0 1335.6 1800.0	127.8 371.0 500.0	37.9 26.3 17.0		132	84		
	B	430.0 1270.8 1610.0	119.4 353.0 447.2	32.5 22.5 15.5		110	82		
	C	410.0 1188.0 1400.0	113.9 330.0 388.9	27.5 17.8 17.1		90	78		
350-440(I)		1000.0 2745.0 3500.0	277.8 762.5 972.2	59.0 43.5 31.0	1480	450	87.5	8.5	128.5
	A	950.0 2635.2 3450.0	263.9 732.0 958.3	50.5 35.0 22.0		355	85.5		
	B	900.0 2563.2 3250.0	250.0 712.0 902.8	43.0 27.5 18.5		280	84		
	C	890.0 2484.0 3200.0	147.2 690.0 888.9	36.0 21.5 13.0		220	81		

泵型号	流量Q		扬程 (m)	转速 (rpm)	功率 (kW)	效率 (%)	心需汽蚀余量 (m)	泵重 (kg)	
	(m <sup>3</sup> /h)	(L/s)							
350-440		750.0 2235.0 3000.0	208.3 620.8 833.8	59.0 42.5 30.0	1480	355	86.5	6.5	1285
	A	700.0 2088.0 2750.0	194.4 580.0 763.9	51.5 36.0 25.0		280	84.5		
		680.0 1987.2 552.0	188.9 552.0 30.0	45.0		250	82		

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

		2400.0	666.7	23.0					
	C	650.0	180.6	38.0					
		1847.6	516.0	25.0		200	78.5		
		2010.0	558.3	22.0					
350-520(I)		1350.0	375.0	94.0	1480	630	88.5	6.7	1395
		2610.0	725.0	70.0					
		3700.0	1027.8	48.3					
	A	1100.0	305.6	82.0		560	87		
		2430.0	675.0	60.0					
		3500.0	972.2	42.0					
	B	750.0	208.3	73.0		400	86		
		2232.0	620.0	50.0					
		2850.0	791.7	37.0					
	C	505	140.3	61		315	79		
		2070	575	38					
		2350	652.8	33.2					
350-520		850	236.1	92	148	630	88	7	1395
		2450	680.6	67					
		3350	930.6	47.5					
	A	800	222.2	81.5		500	87		
		2268	630	59.5					
		3200	888.9	38					
	B	750	208.3	81.4		400	85		
		2088	580	50					
		2850	791.7	34.5					
	C	700	194.4	60		315	83		
		1944	540	41.5					
		2500	694.4	30.5					
350-640		1470	408.03	138.5	1480	1000	85	6.9	1500
		2160	600	126.2					
		2800	777.8	107					
	A	1290	358.3	128		900	84		
		2000	556	116					
		2600	722	98.3					
	B	1185	329.2	117.8		800	82		
		1920	533.3	106					
		2500	694.4	88.5					
	C	1110	308.3	107.8		710	80		
		1830	508.3	95.6					
		2380	661	78					
	D	1050	291.7	93.8		560	78		
		1695	470.8	83					
		2200	611	68					

S0W 系列单级双吸泵系水平中开蜗壳式离心泵

400-550 (I)		1535 1635 3420	426.3 731.9 950	98 86 70.8	1480	800	85	7	1600
	A	1470 2520 3270	408.3 700 908.3	91 79 63.9		710	83		
	B	1420 2418 3140	394 671.6 872	82.6 71.8 56.8		630	81		
	C	1400 2311.5 3015	388.9 642 837.5	76 64 49		630	79		
	D	1380 2235.6 2900	383.3 62.1 805.6	69 57.8 43.8		560	77		
400-550		1320 2190 2850	366.7 608.3 791.7	77 63.8 47.2	1480	500	86	5.9	1600
	A	1280 2045.5 2660	355.6 568.2 738.9	69.8 57.8 43.8		450	84		
	B	1230 1882 2450	341.7 522.7 680.6	61.2 51.2 39		400	82		
	C	1211 1767.6 2300	336.4 49.1 638.9	53.2 45 34		315	80		

泵型号	流量Q		扬程 (m)	转速 (rpm)	功率 (kW)	效率 (%)	心需汽蚀余量 (m)	泵重 (kg)	
	(m <sup>3</sup> /h)	(L/s)							
400-600		1571 2502 3250	436.4 695 902.8	101.2 90.2 68	1480	800	86	6.9	2100
	A	1508 2422 3100	41.9 627.7 861	93.2 81.8 63		710	84		
	B	1500 2354 3000	416.7 654 833.3	86 74 54		630	82		
	C	1470 2225.5 2750	410 618.2 764	78.8 68 51.8		560	80		

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	D	1505 2127.6 2500	418.2 59.1 722	69 59.8 47		500	78		
400-600(I)		1919 3176.5 4100	533 882.4 1139	129.7 113 93.6	1480	1250	86	7.5	2100
	A	1780 3007 3910	494.4 835.3 1086	119 103.6 83.6		1120	84		
	B	1740 2922.4 3800	483.3 811.8 1055.6	109.2 93 70.8		1000	82		
	C	1600 2732 3550	444.4 758.8 986	99.8 83.7 63		900	80		
	D	1530 2641.6 3380	425 706 938.9	90 74 57		800	78		
500-520(I)		1900 3217.5 3960	527.8 893.8 1100	33.2 25 17.7	980	280	87	4.8	1528
	A	1830 3088 3800	508.3 857.8 1055.6	30.5 23 16.3		250	86		
	B	1750 2964.5 3650	486 823.3 1013.9	28.6 21 15.3		220	84		
	C	1680 2846 3485	466.7 790.6 968	26 18.4 13		200	82		
	D	1600 2732 3180	444.4 758.9 883.3	23.8 16.3 11.75		180	80		
500-520		1480 2777 3600	411 771.4 1000	31.3 22.5 14	980	180	80	4.3	1528
	A	1400 2638 3420	388.9 732.8 950	27.8 19.5 12.2		220	86		
	B	1250 2484 3000	347.2 690 833.3	22 15.6 11.2		200	84		
		1160	322.2	18.5		160	81		

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	C	2178.5 2790	605.1 775	13.8 9.2					
500-650(I)		1850 3510 4500	513.9 975 1250	52.5 41.5 31	980	132	78	5.7	2301
	A	1800 3352.5 4230	500 931 1175	49.8 38.7 28.5		500	88.5		
	B	1740 3172.5 4000	483.3 88.1 1111.7	46.4 36 26.5		450	86		
	C	1660 3015 3830	461.1 837.5 1064	42.2 33.2 25		400	84		
	D	1560 2767.5 3600	433.3 768.8 1000	37.6 29.7 21.8		355	82		
500-650		1820 2992 3890	505.6 831.3 1080	41.8 33.7 23.2	980	315	80	4.8	2301
	A	1730 2835 3695	480.6 787.5 1026	37.8 30.2 21		355	87		
	B	1635 2722.5 3490	454 756.3 969.4	34 27.7 19		315	86		

泵型号		流量Q		扬程 (m)	转速 (rpm)	功率 (kW)	效率 (%)	必需汽蚀余量 (m)	泵重 (kg)
		(m <sup>3</sup> /h)	(L/s)						
500-650	C	1535	426.4	29	980	250	78	4.8	2301
		2642.5	706	24					
		3280	911	17					
500-710(I)		2300	638.9	73.1	980	900	88.5	5.8	2967
		3852	1070	64.4					
		5040	1400	54					
	A	2200	611.1	67.2		800	87		
		3672	1020	592					
		4840	1344.4	47.1					
	B	2100	583.3	60.3		710	85		
		3470.4	964	53					
		4320	1200	43					
		2000	555.6	56.4					

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	C	3204 3960	890 1100	47.7 39		560	83		
	D	1920 3024 3550	533.3 840 986.1	50 42 34.2		500	81		
500-710		1800 3006 3900	500 835 1083	60 49 35.6	980	560	87	5.5	2967
	A	1710 2812.5 3700	475 78 1.3 1027.8	53.6 44.2 31.2		450	85		
	B	1615 2632.5 3375	448.6 731.3 937.5	47.7 39.3 29		400	83		
	C	1518 2407.5 3175	421.7 668.7 882	41.5 34.6 26		355	79		
500-800(I)		2590 3996 5190	719.4 1110 1441.7	88.7 80.6 67.9	980	1120	89	6.9	3483
	A	2460 3600 4680	683.3 1000 1300	78.4 72.8 61.8		900	87		
	B	2340 3240 4100	650 890 1138.9	69.8 65.3 57		800	85		
	C	2200 2880 3600	611.1 800 1000	61 58 52		630	83		
500-800		2385 3474 4600	622.5 965 1277.8	70.7 62.5 47.5	980	800	88	5.2	3483
	A	2265 3330 4370	629 925 1213.9	63.1 55.8 44		710	86		
	B	2150 3150 4150	597.2 87 5 1152.8	56.2 49.6 39.2		560	84		
	C	2050 2970 3940	569.7 825 1094	48 43.6 35.8		500	80		
500-860(I)		2520	700	124	980			6.9	4659

4183.2 1162 111.2 1600 89

SOW 系列单级双吸泵系水平中开蜗壳式离心泵

	A	5440	1511	96.2	980	1400	87	5.5	4659
		2380	661.1	112.4					
		3996	1110	100.7					
	B	5140	1428	86					
		2250	625	102.4					
		3780	1050	90.4					
	C	4870	1352.8	77.5					
		2115	587.5	90.4					
		3528	980	80.4					
	500-860		4320	1300		70.6			
			2400	666.7		99.6			
			3600	1000		90			
A		4680	1300	73					
		2300	638.9	93.4					
		3492	970	82.9					
B		4500	1250	68					
		2200	611.1	87.2					
		3384	940.3	77.2					
C		4300	1194.4	63.8					
		2090	580.6	81					
		3204	890	71.5					
D	4085	1134.7	59						
	1985	551.4	75						
	3081.6	856	65.8						
		3850	1069	55.6					