

SH 型单级双吸清水离心泵性能参数

泵型号	流量 Q (米 ³ /时)	扬程 H (米)	转速 n (转/分)	功率N (千瓦)		效率 η (%)	允许吸上 真空高度 (米)	重量 (公斤)
				轴功率	配用电机			
6Sh-6	126	84	2900	40	Y250M-2 55	72	5.0	150
	162	78		46.5		74		
	198	70		52.4		72		
6Sh-6A	111.6	67	2900	30	Y225M-2 45	68	5.0	150
	144	62		33.8		72		
	180	55		38.54		70		
6Sh-9	130	52	2900	25.3	Y200L2-2 37	73.9	5.0	145
	170	47.6		27.6		79.8		
	220	35		31.3		67		
6Sh-9A	102	43.8	2900	18.5	Y200L1-2 30	70	4.5	145
	144	40		20.9		75		
	180	35		24.5		72		
8Sh-6	180	100	2900	81.8	Y315S-2 110	60	5.0	309
	234	93.5		86.3		69		
	288	82.5		91.1		71		
8Sh-9	213	69	2900	55	Y280S-2 75	74	5.3	265
	288	62.5		61.1		79.5		
	351	50		67.8		70.5		
8Sh-9A	180	54.5	2900	41	Y250M-2 55	65	5.5	265
	270	46		48.3		70		
	324	37.5		51		65		
8Sh-13	216	48	2900	24.9	Y225M-2 45	81	5	219
	288	41.3		38.1		85		
	346	35		40.2		81		

SH 型单级双吸清水离心泵

8Sh-13A	198	43	2900	30.5	Y200L2-2 37	76	5.2	219
	270	36		33.1		80	4.3	
	310	31		34.4		76	3.0	
10Sh-9	360	42.5	1450	55.5	Y280S-4 75	75	6.0	428
	486	38.5		61.5		83		
	612	32.5		67.7		80		
10Sh-9A	324	35.5	1450	40.2	Y250M-4 55	78	6.0	428
	378	30.5		45.7		85		
	466	25		47.8		28		
10Sh-13	360	27	1450	33.1	Y225M-4 45	80	6.0	420
	486	23.5		36.2		86		
	576	19		36.4		82		
10Sh-13A	342	22.2	1450	25.8	Y225S-4 37	80	6.0	420
	414	20.3		27.6		85		
	482	17.4		28.6		80		
10Sh-19	360	17.5	1450	21.4	Y200L1-4 30	80	6.0	405
	486	14		21.8		85		
	576	11		22.1		78		
10Sh-19A	320	13.7	1450	15.4	Y180M-4 18.5	78	6.0	405
	432	11		15.8		82		
	503	8.6		15.8		75		
12Sh-6	590	98	1450	213	300	74	5.4	847
	792	90		250		77.5	4.5	
	936	82		279		75	3.5	
12Sh-6A	576	86	1450	190	260	71	5.5	845
	756	78		217		74	4.7	
	918	70		246		71	3.6	

SH 型单级双吸清水离心泵

泵型号	流量 Q (米 ³ /时)	扬程 H (米)	转速 n (转/分)	功率N(千瓦)		效率 η (%)	允许吸上 真空高度 (米)	重量 (公斤)
				轴功率	配用电机			
12Sh-6B	540	72	1450	151	225	70	5.6	845
	720	67		189		73	4.9	
	900	56		200		70	3.9	
12Sh-9	576	65	1450	127.5	Y315M1-4 185	80	4.5	809
	792	58		159		83.5		
	972	50		167.5		79		
12Sh-9A	530	55	1450	99.2	Y315S-4 160 Y315M2-4 160	80	4.5	809
	730	49		115.6		83		
	893	42		131		78		
12Sh-9B	504	47.2	1450	82.5	Y315M1-4 132	79	4.5	809
	684	43		97.7		82		
	835	37		108		78		
12Sh-13	612	38	1450	76.2	Y280M-4 90	83	4.5	709
	792	32.2		80.3		86.5		
	900	28		86		80		
12Sh-13A	551	31	1450	58.1	Y280S-4 75	80	4.5	709
	720	26		60.7		84		
	810	24		68		78		
12Sh-19	612	23	1450	47.9	Y250M-4 55	80	4.5	660
	792	19.4		51		82		
	935	14		47.6		75		
12Sh-19A	504	20	1450	33.5	Y225M-4 45	82	4.5	660
	720	16		36.9		85		
	900	11.5		35.3		80		

SH 型单级双吸清水离心泵

14Sh-6	850	140	1470	462	680	70	3.5	1580
	1250	125		545		78		
	1498	107		590		74		
14Sh-6A	803	125	1470	391	570	70	3.5	1580
	1181	112		462		78		
	1411	96		506		73		
14Sh-6B	745	108	1470	313	500	70	3.5	1580
	1098	96		373		77		
	1314	82		402		73		
14Sh-9	972	80	1450	271	360	78	3.5	1200
	1260	75		314		82		
	1440	65		319		80		
14Sh-9A	900	70	1450	226	300	76	3.5	1200
	1170	65		256		81		
	1332	56		257		79		
14Sh-9B	828	59	1450	178	260	75	3.5	1200
	1080	55		202		80		
	1224	47.5		206		77		
14Sh-13	972	50	1470	164	220	81	3.5	1105
	1260	43.8		177		85		
	1476	37		189		79		
14Sh-13A	864	41	1470	121	155	80	3.5	1105
	1116	36		130		84		
	1332	30		136		80		

SH 型单级双吸清水离心泵