

S 型单级双吸泵壳中开之离心泵性能参数

250S39	360	42.5	1450	54.8	75	76	3.2
	485	39		61.5		83.6	
	612	32		68.6		79	
250S39A	324	35.5	1450	42.5	55	74	3.2
	468	30.5		49.3		79	
	576	25		50.9		77	
250S24	360	27	1450	33.1	4.5	80	3.5
	485	24		36.9		85.8	
	576	19		36.4		82	
250S24A	342	22.2	1450	25.8	37	80	3.5
	414	20.3		27.6		83	
	482	17.4		28.6		80	
250S14	360	16	1450	19.6	30	80	3.8
	485	14		21.5		85.8	
	576	11		22.1		78	
250S14A	320	13.7	1450	15.4	18.5	78	3.8
	432	11		15.8		82	
	504	8.6		15.8		75	
300S110	590	113	1450	248.6	440	73	4
	790	110		295.7		80	
	936	105		326.3		82	
300S90	590	93	1450	202	315	74	4
	790	90		242.8		79.6	
	936	82		279		75	
300S90A	576	86	1450	190	280	71	4
	756	78		217		74	
	918	70		247		71	
300S90B	540	72	1450	151	220	70	4
	720	67		181		73	
	900	57		200		70	
300S58	576	63	1450	136	180	72.7	4.4
	790	58		149.9		84.2	
	972	50		165.5		80	
300S58A	529	53	1450	99.9	160	76.4	4.4
	720	49		118.6		81	
	893	42		131		78	
300S58B	504	46	1450	88.8	132	71.1	4.4
	684	43		100		80	
	835	37		108		78	

S 型单级双吸泵壳中开之离心泵

300S32	612	36	1450	75	110	80	4.6
	790	32		79.2		86.8	
	900	28		86		80	
300S32A	551	31	1450	58.1	75	80	4.6
	720	26		60.7		84	
	810	24		68		78	
300S19	612	22	1450	45.9	55	80	5.2
	790	19		47		86.8	
	935	16		47.6		85.6	
300S19A	504	20	1450	38.7	45	71	5.2
	720	16		39.2		80	
	829	13		39.1		75	
300S12	612	14.5	1450	30.2	37	80	5.5
	790	12		30.4		84.8	
	900	10		33.1		74	
300S12A	522	11.8	1450	23.3	30	72	5.5
	684	10		23.9		78	
	792	8.7		24.7		76	
350S125	850	140	1450	462	710	70	5.4
	1260	125		534		80.5	
	1660	100		623		72.5	
350S125A	803	125	1450	391	630	70	5.4
	1181	112		462		78	
	1570	90		550		70	
350S125B	745	108	1450	313	500	70	5.4
	1098	96		373		77	
	1458	77		422		72.5	
350S75	972	80	1450	271	355	78	5.8
	1260	750		303		85.2	
	1440	65		319		80	
350S75A	900	70	1450	220	280	78	5.8
	1170	65		247		84	
	1332	56		257		79	
350S75B	828	59	1450	177	220	75	5.8
	1080	55		197		82	
	1224	47.5		206		77	
350S44	972	50	1450	164	220	81	6.3
	1260	44		173		87.5	
	1476	37		189		79	
350S44A	864	41	1450	121	160	80	6.3
	1116	36		131		84	
	1332	30		136		80	

S 型单级双吸泵壳中开之离心泵

350S26	972	30	1450	99.7	132	79.7	6.7
	1260	26		102		87.5	
	1440	22		105		82	
350S26A	864	26	1450	76.5	90	80	6.7
	1116	21.5		78.8		83	
	1296	16.5		80		73	
350S16	972	20	1450	64	75	83	7.1
	1260	16		64.5		85.3	
	1440	13.4		71		74	
350S16A	864	16	1450	51	55	74	7.1
	1044	13.4		48.8		48	
	1260	10		49		70	
500S98	1620	114	970	644.8	800	78	4
	2020	98		678		79.5	
	2340	79		680.3		74	
500S98A	1500	96	970	509.3	630	77	4
	1872	83		540		78.5	
	2170	67		542.4		73	
500S98B	1400	86	970	431.4	560	6	4
	1746	74		452		78	
	2020	59		432.8		75	
500S59	1620	68	970	379.7	450	79	4.5
	2020	59		391		83	
	2340	47		374.4		80	
500S59A	1500	57	970	315	400	74	4.5
	1872	49		333		75	
	2170	39		320		72	
500S59B	1400	46	970	240.2	315	73	4.5
	1746	40		257		74	
	2020	32		247.9		71	
500S35	1620	40	970	207.6	280	85	4.8
	2020	35		219		88	
	2340	28		209.9		85	
500S35A	1400	31	970	144	220	82	4.8
	1746	27		151		85	
	2020	21		116.9		84	
500S22	1620	24.5	970	140.4	185	77	5.2
	2020	22		144.1		84	
	2340	19.4		145.4		85	

S 型单级双吸泵壳中开之离心泵

500S22A	1400	20	970	103	132	74	5.2
	1746	17		101		80	
	2020	14		93.9		82	
500S13	1620	15	970	83.8	110	79	5.7
	2020	13		86.2		83	
	2340	10.4		82.8		80	
600S75	3170	75	970	727	800	89	7.5
600S75A	2880	65	970	580	630	88	7.5
600S47	2500	56	970	460	560	83	7.5
	3170	47		465		88	
	3500	38		426		80	
600S32	2520	37	970	295	400	86	7.5
	3170	32		310		89	
	3960	22		279		85	
600S32A	2304	31.5	970	235	280	89	7.5
	2880	27		238			
	3600	20		231			
600S22	3170	22	970	223	280	85	7.5
600S22A	2880	18.2	970	168.5	200	84.5	7.5

S 型单级双吸泵壳中开之离心泵